

1 Identification

Product identifier

Product name: Isobutanol

Stock number: 22908

CAS Number:
78-83-1

EC number:
201-146-0

Index number:
603-108-00-1

Relevant identified uses of the substance or mixture and uses advised against.

Identified use: SU24 Scientific research and development

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Alfa Aesar
Thermo Fisher Scientific Chemicals, Inc.
30 Bond Street
Ward Hill, MA 01835-8099
Tel: 800-343-0660
Fax: 800-322-4757
Email: tech@alfa.com
www.alfa.com

Information Department: Health, Safety and Environmental Department

Emergency telephone number:

During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660. After normal business hours, call Carechem 24 at (866) 928-0789.

2 Hazard(s) identification

Classification of the substance or mixture in accordance with 29 CFR 1910 (OSHA HCS)



GHS02 Flame

Flam. Liq. 3 H226 . . . Flammable liquid and vapour.



GHS05 Corrosion

Eye Dam. 1 H318 . . . Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 . . . Causes skin irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Hazards not otherwise classified No information known.

Label elements

GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS)

Hazard pictograms



GHS02 GHS05 GHS07

Signal word

Danger

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P310 Immediately call a POISON CENTER/doctor.

P362 Take off contaminated clothing and wash before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

WHMIS classification

B2 - Flammable liquid

D2B - Toxic material causing other toxic effects



Classification system

HMIS ratings (scale 0-4)

(Hazardous Materials Identification System)

HEALTH 2 Health (acute effects) = 2

FIRE 3 Flammability = 3

REACTIVITY 1 Physical Hazard = 1

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

Product name: Isobutanol

(Contd. of page 1)

vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Substances

CAS# Description:
78-83-1 Isobutanol

Identification number(s):

EC number: 201-148-0

Index number: 603-108-00-1

4 First-aid measures

Description of first aid measures

After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm.

Seek immediate medical advice.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

Seek immediate medical advice.

After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing Seek medical treatment.

Information for doctor

Most important symptoms and effects, both acute and delayed

Causes skin irritation.

Causes serious eye damage.

May cause respiratory irritation.

May cause drowsiness or dizziness.

Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents Carbon dioxide, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards arising from the substance or mixture If this product is involved in a fire, the following can be released:

Advice for firefighters

Protective equipment:

Wear self-contained respirator.

Wear fully protective impervious suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

Environmental precautions: Do not allow product to reach sewage system or any water course.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Prevention of secondary hazards: Keep away from ignition sources.

Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling

Precautions for safe handling

Keep container tightly sealed.

Store in cool, dry place in tightly closed containers.

Ensure good ventilation at the workplace.

Information about protection against explosions and fires:

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

Keep ignition sources away.

Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Store away from oxidizing agents.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed containers.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems:

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Control parameters

Components with limit values that require monitoring at the workplace:

78-83-1 Isobutanol (100.0%)

PEL (USA) Long-term value: 300 mg/m³, 100 ppm

REL (USA) Long-term value: 150 mg/m³, 50 ppm

TLV (USA) Long-term value: 152 mg/m³, 50 ppm

EL (Canada) Long-term value: 50 ppm

EV (Canada) Long-term value: 150 mg/m³, 50 ppm

Additional information: No data

(Contd. on page 3)
USA

Product name: Isobutanol

(Contd. of page 2)

Exposure controls

Personal protective equipment

General protective and hygienic measures

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Maintain an ergonomically appropriate working environment.

Breathing equipment: Use suitable respirator when high concentrations are present.

Protection of hands:

Impervious gloves

Check protective gloves prior to each use for their proper condition.

The selection of suitable gloves not only depends on the material, but also on quality. Quality will vary from manufacturer to manufacturer.

Eye protection: Tightly sealed goggles

Body protection: Protective work clothing.

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form: Liquid
Color: Colorless
Odor: Sweet
Odor threshold: Not determined.

pH-value (80 g/l) at 20 °C (68 °F): 7

Change in condition

Melting point/Melting range: -108 °C (-162 °F)
Boiling point/Boiling range: 107-108 °C (225-226 °F)
Sublimation temperature / start: Not determined

Flash point: 28 °C (82 °F)
Flammability (solid, gaseous): Not determined.
Ignition temperature: 390 °C (734 °F)
Decomposition temperature: Not determined
Auto igniting: Not determined.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures is possible.

Explosion limits:

Lower: 1.7 Vol %
Upper: 12 Vol %
Vapor pressure at 20 °C (68 °F): 4-40 hPa (3-30 mm Hg)
Density at 20 °C (68 °F): 0.802 g/cm³ (6.693 lbs/gal)
Relative density: Not determined.
Vapor density: Not determined.
Evaporation rate: Not determined.

Solubility in / Miscibility with

Water at 20 °C (68 °F): 100 g/l
Partition coefficient (n-octanol/water): Not determined.

Viscosity:

dynamic at 20 °C (68 °F): 3.95 mPas
kinematic: Not determined.

Other information No further relevant information available.

10 Stability and reactivity

Reactivity No information known.

Chemical stability Stable under recommended storage conditions.

Thermal decomposition / conditions to be avoided: Decomposition will not occur if used and stored according to specifications.

Possibility of hazardous reactions Reacts with strong oxidizing agents

Conditions to avoid No further relevant information available.

Incompatible materials: Oxidizing agents

11 Toxicological information

Information on toxicological effects

Acute toxicity: The Registry of Toxic Effects of Chemical Substances (RTECS) contains acute toxicity data for this substance.

LD/LC50 values that are relevant for classification:

Oral	LD50	2460 mg/kg (rat)
Dermal	LD50	3400 mg/kg (rabbit)
Inhalative	LC50/4H	2630 mg/m ³ /4H (rabbit)

Skin irritation or corrosion: Causes skin irritation.

Eye irritation or corrosion: Causes serious eye damage.

Sensitization: No sensitizing effects known.

Germ cell mutagenicity: The Registry of Toxic Effects of Chemical Substances (RTECS) contains mutation data for this substance.

Carcinogenicity:

The Registry of Toxic Effects of Chemical Substances (RTECS) contains tumorigenic and/or carcinogenic and/or neoplastic data for this substance.

No classification data on carcinogenic properties of this material is available from the EPA, IARC, NTP, OSHA or ACGIH.

Reproductive toxicity: The Registry of Toxic Effects of Chemical Substances (RTECS) contains reproductive data for this substance.

Specific target organ system toxicity - repeated exposure: No effects known.

Specific target organ system toxicity - single exposure:

May cause drowsiness or dizziness.

May cause respiratory irritation.

Aspiration hazard: No effects known.

Subacute to chronic toxicity: The Registry of Toxic Effects of Chemical Substances (RTECS) contains multiple dose toxicity data for this substance.

Additional toxicological information: To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

Carcinogenic categories

OSHA-Ca (Occupational Safety & Health Administration) Substance is not listed.

Product name: Isobutanol

(Contd. of page 3)



12 Ecological information

Toxicity
Aquatic toxicity: No further relevant information available.
Persistence and degradability No further relevant information available.
Bioaccumulative potential No further relevant information available.
Mobility in soil No further relevant information available.
Additional ecological information:
General notes:
 Do not allow undiluted product or large quantities to reach ground water, water course or sewage system.
 Avoid transfer into the environment.
Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.
Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods
Recommendation Consult state, local or national regulations to ensure proper disposal.
Uncleaned packagings:
Recommendation: Disposal must be made according to official regulations.

14 Transport information

UN-Number DOT, IMDG, IATA	UN1212
UN proper shipping name DOT IMDG, IATA	Isobutanol (Isobutyl alcohol) ISOBUTANOL (ISOBUTYL ALCOHOL)
Transport hazard class(es) DOT	
	
Class	3 Flammable liquids.
Label	3
Class	3 (F1) Flammable liquids
Label	3
IMDG, IATA	
	
Class	3 Flammable liquids.
Label	3
Packing group DOT, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user EMS Number:	Warning: Flammable liquids F-E,S-D
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT Marine Pollutant (DOT):	No
UN "Model Regulation":	UN1212, Isobutanol (Isobutyl alcohol), 3, III

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS)
Hazard pictograms

  
 GHS02 GHS05 GHS07

Signal word Danger

Hazard statements

H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P310 Immediately call a POISON CENTER/doctor.
 P362 Take off contaminated clothing and wash before reuse.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations

All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.
 All components of this product are listed on the Canadian Domestic Substances List (DSL).

(Contd. on page 5)
USA

Product name: Isobutanol

(Contd. of page 4)

SARA Section 313 (specific toxic chemical listings) Substance is not listed.

California Proposition 65

Prop 65 - Chemicals known to cause cancer Substance is not listed.

Prop 65 - Developmental toxicity Substance is not listed.

Prop 65 - Developmental toxicity, female Substance is not listed.

Prop 65 - Developmental toxicity, male Substance is not listed.

Information about limitation of use: For use only by technically qualified individuals.

Other regulations, limitations and prohibitive regulations

Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006. Substance is not listed.

The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed.

Substance is not listed.

Annex XIV of the REACH Regulations (requiring Authorisation for use) Substance is not listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Department issuing SDS: Global Marketing Department

Date of preparation / last revision 10/04/2016 / -

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

vPvB: very Persistent and very Bioaccumulative

ACGIH: American Conference of Governmental Industrial Hygienists (USA)

OSHA: Occupational Safety and Health Administration (USA)

NTP: National Toxicology Program (USA)

IARC: International Agency for Research on Cancer

EPA: Environmental Protection Agency (USA)

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3